

Lithio V 220 EP 2 Long Life



FI

Pitkäikäinen voiteluaine, joka on tarkoitettu laakereiden ja kitkakytkinten voiteluun vaativissa käyttöolosuhteissa metsä-, rakennus- ja maatalouskoneissa.

- vedenkestävä
- hapettumiskestävä
- voiteluaine, jolla on parannettu tarttuvuus
- parannetut EP-ominaisuudet
- lisäsuoja korroosiota vastaan

GB

Long-life grease designed for the lubrication of bearings and friction elements operating under harsh operating conditions in forestry, construction, and agricultural machinery.

- water-resistant
- oxidation-resistant
- grease with increased adhesion
- enhanced EP properties
- additional corrosion protection

Thickener		lithium/calcium
Base fluid		mineral
Texture		smooth
Colour	Visual	red
NLGI Class	ASTM D 217	2
Dropping point	IP 396	180°C
Base oil at 40	ASTM D 7152	220 cSt
Base oil at 100	ASTM D 7152	18 cSt
4-ball weld load	ASTM D2596	3000 N
Penetration 60 strokes	ISO 2137	265-295
Temperature range		-25°C to 120°C, (max 140°C)

DIN 51502: KP2N-30
ISO 6743-9: L-XCDHB2

Art. no
1116.010 – 420 ml
1116.020 – 420 ml – LS
1116.030 – 500 g
1116.050 – 5 kg
1116.070 – 18 kg
1116.080 – 50 kg
1116.090 – 180 kg

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only.
Information and data can be changed without previous notification. This information replaces prior editions.