

Lithio V 460 HD 2



FI

Litiumrasva, joka on tarkoitettu laakereiden ja kitkakytkinten voiteluun vaativissa käyttöolosuhteissa metsä-, rakennus- ja maatalouskoneissa.

- vedenkestävä
- hapettumiskestävä
- rasva, jolla on parannettu tarttuvuus
- parannetut EP-ominaisuudet
- lisäsuoja korroosiota vastaan

GB

Lithium grease designed for the lubrication of bearings and friction elements operating under harsh operating conditions in forestry, construction, and agricultural machinery.

- water-resistant
- oxidation-resistant
- grease with increased adhesion
- enhanced EP properties
- additional corrosion protection

Thickener		lithium
Base fluid		mineral
Texture		smooth
Colour	Visual	brown
NLGI Class	ASTM D 217	2
Dropping point oC	IP 396	230°C
Base oil at 40oC	ASTM D 7152	460 cSt
4-ball weld load	ASTM D2596	4000 N
Penetration 60 strokes	ISO 2137	265-295
Temperature range		-30°C to 140°C

DIN 51502: KP2N-30
ISO 6743-9: L-XCDHB2

Art. no
1127.010 – 420 ml
1127.030 – 500 gr
1127.070 – 18 kg
1127.090 – 180 kg

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only.
Information and data can be changed without previous notification. This information replaces prior editions.