

Lithioplex Synt V 220 EP 2



FI

Korkean lämpötilan monikäyttöinen litiumrasva, joka on tarkoitettu vierintä- ja liukulaakereiden voiteluun korkeissa ja iskuvoimaisissa kuormitusolosuhteissa sekä korkeissa laakerin käyttölämpötiloissa. Rasva sisältää EP-lisäaineita ja on vedenkestävä.

- korkean lämpötilan rasva
- EP-ominaisuudet
- hyvät korroosionesto-ominaisuudet
- korkea mekaaninen stabiilisuus
- hapettumiskestävä

GB

High-temperature, comprehensive lithium grease designed for lubricating rolling and sliding bearings operating under high and impact loads at elevated bearing operating temperatures. The grease contains EP additives and is resistant to water.

- high-temperature grease
- has EP properties
- good anti-corrosion properties
- high mechanical stability
- resistant to oxidation

Thickener		lithium complex
Base fluid		mineral
Texture		smooth
Colour	Visual	red
NLGI Class	ASTM D 217	2
Dropping point	IP 396	272°C
Base oil at 40	ASTM D 7152	220 cSt
Base oil at 100	ASTM D 7152	15 cSt
4-ball weld load	ASTM D2596	2450 N
Penetration 60 strokes	ISO 2137	265-295
Temperature range		-30°C to 160°C

DIN 51502: KP2P-30
ISO 6743-9: L-XCEHB2

Art. no
1310.010 – 420 ml
1310.030 – 500 gr
1310.050 – 5 kg
1313.070- 18 kg
1313.090 – 180 kg

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only.
Information and data can be changed without previous notification. This information replaces prior editions.