

Lithioplex V 220 HP 0

FI

Kestävä litiumrasva, joka on tarkoitettu erittäin raskaissa käyttöolosuhteissa toimivien kitkakomponenttien voiteluun eri teollisuudenaloilla, erityisesti raskaiden kuljetusajoneuvojen akselilaakereiden voiteluun.

- erittäin hyvä tarttuvuus
- erittäin hyvä vedenkestävyys
- korkea mekaaninen stabiilisuus
- erinomaiset kulumisenesto-ominaisuudet

GB

Lithium complex grease with increased durability, designed for lubricating friction elements operating in extremely harsh conditions in various industries, in particular for lubricating axle bearings in heavy goods vehicles.

- very high adhesion
- very good resistance to water washout
- high mechanical stability
- exceptional anti-wear properties



Thickener		lithium complex
Base fluid		mineral
Texture		smooth
Colour	Visual	blue
NLGI Class	ASTM D 217	0
Dropping point	IP 396	242°C
Base oil at 40	ASTM D 7152	220 cSt
Base oil at 100	ASTM D 7152	18 cSt
4-ball weld load	ASTM D2596	3920 N
Penetration 60 strokes	ISO 2137	355-385
Temperature range		-30°C to 160°C

DIN 51502: KPFOP-30
ISO 6743-9: L-XCEHB0

Art. no
1317.010 – 420 ml
1317.030 – 500 gr
1317.050 – 5 kg
1317.070 – 18 kg
1317.080 – 50 kg
1317.090 – 180 kg

The information above is based on current production data and can vary within given tolerances. Temperature range is given as a guideline only.
Information and data can be changed without previous notification. This information replaces prior editions.